

# NON-DETECTABLE MARKING TAPE (6 MIL)

6.0 Mil Virgin Pigmented Polyethylene Film • Rated for Direct Burial for Marking Underground Utility Lines  
 APWA Color-Coded for Representation and Visibility of Buried Utility Line

## DESCRIPTION

**PRO-LINE®** Non-Detectable Marking Tape is used primarily for marking and underground utility structures. **PRO-LINE®** Non-Detectable Marking Tape serves three simple functions: Locate, Identify, and Protect. Non-Detectable Tape is usually the last category of a utility structures design and installation...maintenance and immediate location and identification. **PRO-LINE®** Non-Detectable Marking Tape is APWA Color-Coded to identify the type of utility that is buried below. Non-Detectable Marking Tape is also printed to identify what type of utility is buried below.



*“Helping to Protect Underground Investments and the General Public Since 1992!”*

## STANDARDS & REFERENCES

**PRO-LINE®** Detectable Marking Tape meets or exceeds all applicable ASTM specifications.

- ASTM D2103-05 (Standard Specification for Polyethylene Film and Sheeting)
- ASTM D882-02 (Standard Test Method for Tensile Properties of Thin Plastic Sheeting)
- ASTM D882-75B (Standard Test Method for Tensile Properties of Thin Plastic Sheeting for Elongation)
- ASTM D2578 (Standard Test Method for Wetting Tension of Polyethylene and Polypropylene Films)

## CONSTRUCTION

- **PRO-LINE®** Non-Detectable Marking Tape consists of a minimum 6.0 mil overall thickness, manufactured with virgin polyethylene with color pigments added at point of film extrusion to identify underground utility structures based on the APWA Color-Code .
- **PRO-LINE®** Non-Detectable Marking Tape is printed with big, bold, black lettering to identify what type of utility line is buried below.

TEST DATA	METHOD	VALUE
Thickness	ASTM D2103-05	6.0 mil
Tensile Strength	ASTM D882-02	4,100 psi
Elongation	ASTM D882-75B	700%
Film Pigmentation	APWA Color-Coded	APWA Color-Coded
Message Repeat	Mfg. Specs.	Varies by Legend
Printed Inks	Mfg. Specs.	Flexo 9605
Printability	ASTM D2578	45 Dynes

**\*\*THIS SPEC COVERS WIDTHS OF: 2", 3", 4", 6", 12" and 24" Non-Detectable Marking Tape**